FLEXUS SURR 100

SURROUND SPEAKERS





A MULTIDIMENSIONAL HOME THEATER EXPERIENCE

Thanks to immersive Dolby Atmos technology, the Klipsch Flexus Surround 100 speakers create a true multichannel surround sound setup. Hear music, movies, and games placed in 3D around and above you for realistic, spatial sound.

WALL MOUNTABLE FOR FLEXIBLE PLACEMENT

We're keeping it simple and streamlined: no adapters, no dongles, no speaker wires to fuss with here. Each Flexus Surround Speaker independently plugs into a wall outlet with nothing required in between or laying on the floor.

KLIPSCH TRANSPORT TECH FOR ULTIMATE CONNECTIVITY

Enjoy lightning-quick connections across multiple channels with patented Klipsch Transport technology. Add these Flexus Surrounds and a Flexus Subwoofer (or two) to your Klipsch Flexus Core product for truly epic sound.

PEACE OF MIND TESTING PROCESS

Thoroughly reviewed by a team of trusted engineers, over 1,000 rigorous tests were performed on Flexus products to ensure awesome audio performance and stellar interconnectivity.

SIMPLE SETUP, SLEEK STYLE

Individually powered with no junction boxes or power adapters to conceal, the Flexus Surround Speakers are a streamlined solution for multichannel home theaters. Because the controls, power, and LED lights are hidden below the surface, you don't have any distractions in a pitch-black room - just awesome sound and clean aesthetics.

ECO-CONSCIOUS PACKAGING

We're committed to providing great sound for generations - which is why our packaging is designed to be earth-friendly, with careful consideration to minimize waste and maximize recyclability.

SPECIFICATIONS	
SPEAKER SYSTEM	2.0 Wireless Surround (Pair)
MAX ACOUSTIC OUTPUT	103.5dB @ 1M Anechoic pair
FULL RANGE DRIVER	3" Paper Cone
ENCLOSURE TYPE	Sealed - Plastic, Metal
SYSTEM POWER	50W RMS
FREQUENCY RESPONSE	235Hz - 20kHz
HEIGHT	6.75" (171mm)
WIDTH	4.13" (105mm)
DEPTH	4.31" (109.5mm)
FINISH	Ebony Vinyl
VOLTAGE	100-240V 50/60Hz Internal Power Supply
WEIGHT	2.5lbs (1.13kg) each
INCLUDED ACCESSORIES	(2) 2.0m Right-Angle IEC Power Cord (Region Specific) (1) Flexus Transport Wireless dongle (1) User Manual
MOUNTING	1/4" x 20 Threaded Insert